

◎ビニールチューブ(マークチューブ)規格表◎

内 径(Φ)	肉 厚(mm)	内径公差 (mm)	白 1巻の長さ (m)	黒・透明 1巻の長さ (m)	赤・青・緑・黄・橙 水色・ピンク(m)
2.0	0.4	±0.15	200	200	
2.5	0.4	±0.15	200	200	
2.8	0.4	±0.15	200		
3.0	0.45	±0.2	200	200	
3.2	0.45	±0.2	200	300	300
3.3	0.45	±0.2	200		
3.4	0.45	±0.2	200		
3.5	0.45	±0.2	200		
3.6	0.45	±0.2	200		300
3.8	0.45	±0.2	200		
4.0	0.45	±0.2	200	200	
4.2	0.45	±0.2	200		
4.5	0.45	±0.2	200		
5.0	0.45	±0.2	200	200	
5.2	0.45	±0.2	200		
5.5	0.45	±0.2	200		
6.0	0.45	±0.2	200	200	
6.2	0.45	±0.2	200		
6.5	0.45	±0.2	200		
7.0	0.45	±0.2	200	200	
8.0	0.45	±0.2	100	100	
9.0	0.45	±0.2	100	100	
10.0	0.45	±0.2	100	100	
11.0	0.45	±0.2	100		
12.0	0.5	±0.3	100	100	
13.0	0.5	±0.3	100		
14.0	0.5	±0.3	100	100	
15.0	0.5	±0.4	100	100	
16.0	0.5	±0.4	100		

SOLDERLESS TERMINALS & CABLE ACCESSORIES



有限会社石田電業社 Contact Us TEL 045-585-3590
info@ishida-dengyosha.co.jp